



General Description

The HC3404 combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is suitable for use as a load switch or in PWM applications.

Features

V_{DS}	30V
I_D (at $V_{GS}=10V$)	5.8A
$R_{DS(ON)}$ (at $V_{GS}=10V$)	21m Ω (Typ)
$R_{DS(ON)}$ (at $V_{GS}=4.5V$)	30m Ω (Typ)

SOT23



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units	
Drain-Source Voltage	V_{DS}	30	V	
Gate-Source Voltage	V_{GS}	± 20	V	
Drain Current-Continuous	TC=25 $^\circ\text{C}$	I_D	5.8	A
	TC=100 $^\circ\text{C}$	I_D	4.5	A
Drain Current – Pulsed	I_{DM}	23	A	
Maximum Power Dissipation	P_D	1.4	W	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	$^\circ\text{C}$	

Thermal Characteristics

Parameter	Symbol	Typ	Max	Unit
Thermal Resistance junction-case	$R_{\theta Jc}$		1.1	$^\circ\text{C}/\text{W}$
Thermal Resistance junction-to-Ambient	$R_{\theta JA}$		62	$^\circ\text{C}/\text{W}$

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
STATIC PARAMETERS						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V			1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.6	2.5	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =4.0A		21	25	mΩ
		V _{GS} =4.5V, I _D =3.0A		30	40	mΩ
DYNAMIC PARAMETERS						
C _{ISS}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, F=1.0MHz		450		pF
C _{OSS}	Output Capacitance			65		pF
C _{RSS}	Reverse Transfer Capacitance			54		pF
SWITCHING PARAMETERS						
t _{d(on)}	Turn-on Delay Time	V _{GS} =10V V _{DS} =15V R _L =2.6Ω R _{GEN} =3Ω		2.6		nS
t _r	Turn-on Rise Time			8.5		nS
t _{d(off)}	Turn-Off Delay Time			18		nS
t _f	Turn-Off Fall Time			5		nS
Q _g	Total Gate Charge	V _{DS} =15V, I _D =3A, V _{GS} =4.5V		3.7		nC
Q _{gs}	Gate-Source Charge			1.4		nC
Q _{gd}	Gate-Drain Charge			1.5		nC
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _{SD} =1A		0.72	1.3	V
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.5		Ω

Note:

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width ≅ 300us , duty cycle ≅ 2%.
3. Essentially independent of operating temperature.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3 Drain-Source On-Resistance




Figure 4 Drain-Source On-Resistance




Figure 5 Rdson vs Vgs




Figure 6 Gate Charge

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7 Capacitance vs Vds




Figure 8 Safe Operation Area








Figure 9 Normalized Maximum Transient Thermal Impedance



Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



SOT23 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Max	Min	Max	Min
A	1.150	0.900	0.045	0.035
A1	0.100	0.000	0.004	0.000
A2	1.050	0.900	0.041	0.035
b	0.500	0.300	0.020	0.012
c	0.150	0.080	0.006	0.003
D	3.000	2.800	0.118	0.110
E	1.400	1.200	0.055	0.047
E1	2.550	2.250	0.100	0.089
e	0.95 TYP.		0.037 TYP.	
e1	2.000	1.800	0.079	0.071
L	0.55 REF.		0.022 REF.	
L1	0.500	0.300	0.020	0.012
L2	0.25 TYP.		0.01 TYP.	
θ	8°	0°	8°	0°